



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® DRYDex® Spackling

PRODUCT DESCRIPTION

DAP® DRYDex® Spackling provides a unique dry time color indicator that verifies when the patched surface is dry and ready to be sanded and painted, thus providing a smoother finished surface in a shortened amount of time. DAP DRYDex Spackling may be used to fill holes and cracks in surfaces such as drywall, plaster, wood, brick, and stone. Its ready-to-use formula spreads easily for fast, professional repairs that will not crack, crumble, or flake. DRYDex dries hard, sands easily and can be painted.



PACKAGING	COLOR	UPC
5.5 oz Tube	Pink to White	7079812337
½ Pint	Pink to White	7079812328
Pint	Pink to White	7079812348
Quart	Pink to White	7079812330
Gallon	Pink to White	7079812347

KEY FEATURES & BENEFITS

- America's #1 Seller
- Dry Time Indicator – Goes on Pink Dries White
- Patch & Prime in One Step
- Won't Shrink or Crack
- Durable
- Eliminate Errors
- Interior/Exterior use

SUGGESTED USES

Ideal for filling holes, cracks, dents, and defects on:

- Drywall
- Plaster
- Wood
- Stone
- Brick



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- Do not apply when temperatures are below 50°F.
- **DO NOT USE AS A SKIM COAT.**
- **Do not use on wear surfaces or wear expansion & contraction occur**
- For exterior/moisture exposed applications, first apply waterproof primer, then apply waterproof coating (prior to moisture exposure).
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

APPLICATION

1. Surface must be clean, dry and free of all foreign material.
2. Apply in temperatures above 50F.
3. Stir thoroughly before use.
(When using the 5.5 oz squeeze tube, knead tube prior to use. Remove cap and cut nozzle to desired opening size.)
4. Apply with a clean putty knife.
5. One application is usually sufficient for small repairs less than 1/8" in depth.
6. Press spackling into hole/crack with putty knife, drawing firmly across the surface, removing excess material.
7. For repairs > 1/8", apply multiple thin layers allowing for full drying between each layer.
8. Spackling will change color to white when surface can accept a second application or is ready to be sanded or painted in approximately 1 to 5 hours (depending on temperature, humidity and depth of fill).
9. For a smoother finish, dip putty knife in water and lightly smooth spackling.
10. For exterior/moisture exposed applications, apply waterproof coating prior to moisture exposure.
11. Immediately clean up wet product with water. Dry product must be scraped or sanded away.
12. Wet sanding is recommended to avoid generation of dust.

NOTE: To retain the effectiveness of the dry time indicator, keep the container tightly closed after use & store away from extreme heat or cold.

NOTE: To retain the effectiveness of the dry time indicator, keep the container tightly closed after use.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	15.7 pounds
Solids	77% by weight
Application Temperature	50°F or higher
Service Temperature	0°F to 150°F
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	1 to 5 hours depending on temperature, humidity, and depth of fill

CLEAN UP & STORAGE

Immediately clean up wet product with water. Dry product must be scraped or sanded away. NOTE: To retain the effectiveness of the dry time indicator, keep the container tightly closed after use & store away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufacturer: DAP GobaI Inc., 2400 Boston Street, Baltimore, Maryland 21224 **Usage**

Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert" **Order**

Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com