



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® Weldwood® Landau Top & Trim Contact Cement Spray Adhesive

### PRODUCT DESCRIPTION

DAP® Weldwood® Landau Top & Trim Spray Adhesive is a web formula that provides a long-lasting permanent bond on contact. When cured Landau Top & Trim is high heat resistant, water resistant, and creates a flexible bond. It is ideal for use on automotive interiors, laminate work, & many other demanding jobs.



PACKAGING	COLOR	UPC
14 OZ NET WT.	Clear	7079800127

### KEY FEATURES & BENEFITS

- Web spray
- Provides a permanent bond on contact
- Interior & exterior formula
- Ready to bond in 1-3 minutes

### SUGGESTED USES

Adheres to:

- Foam
- Upholstery Fabric
- Upholstery Vinyl
- Plastics
- Paper
- Carpeting
- Laminate
- Felt
- Metal
- Cardboard



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## APPLICATION

**SAFETY FIRST! PRODUCT IS EXTREMELY FLAMMABLE WHILE DISPENSING! READ AND UNDERSTAND ALL OF THE PRECAUTIONARY MEASURES FOR USE, HANDLING, STORAGE AND DISPOSAL CONTAINED IN THE PRODUCT LABEL AND SAFETY DATA SHEET (SDS).**

### PREPARATION:

1. Extinguish all ignition sources during use and cure.
2. Shake well for 1-2 minutes before using.
3. Be sure surfaces to be bonded are clean, dry, and free of all foreign materials.
4. Remove red applicator lock from spray can by sliding upwards and discarding.

### APPLICATION:

1. Wear safety glasses and use in well-ventilated areas.
2. Hold can 6-8 inches from the surface to be sprayed.
3. Keep can moving while spraying to get an even film of adhesive on the surface to be bonded.
4. More than one coat may be required on absorbent/porous surfaces. Test application materials and applications prior to use.
5. Spray both surfaces and allow to dry to a tack.
6. Allow up to 5-10 minutes prior to bonding, make bond while the adhesive is aggressively tacky.

### AFTER USE:

1. Store glued assembly out of direct sunlight and in stable conditions until fully dried (approximately 24 hours).
2. Clean spray tip by inverting can and spraying until no more adhesive is present or using a mineral spirits or acetone.
3. Clean excess wet adhesive from surfaces and tools with mineral spirits. Dried adhesive must be cut or scraped away. Clean hands with warm water and soap. DO NOT use solvents to remove product from skin. Store container in cool, dry place away from extreme heat or cold.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Synthetic Rubber
Open Time:	Up to 30 min
Volatile:	Organic solvent
Application Temperature:	55°F to 95°F
Service Temperature Range:	0°F to 180°F
Coverage:	Up to 79 sq. ft. per can at 1 gram per sq.ft. on a single surface. Coverage will vary depending on porosity of substrates.
Odor:	Solvent
Freeze Thaw Stability:	Stable
Shelf Life:	18 months

## CLEAN UP & STORAGE

Clean excess wet adhesive from surfaces and tools with mineral spirits. Dried adhesive must cut or scraped away. Clean hands with warm water and soap. DO NOT use solvents to remove product from skin. Store container in cool, dry place away from extreme heat or cold.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS sheet by visiting our website at [dap.com](http://dap.com) or by calling 888-DAP-TIPS.

## LIMITED WARRANTY

If product fails to perform as directed, call 888-DAP-TIPS within one year of purchase with your sales receipt and product container available for replacement or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**