



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® All-Purpose Stucco Patch (Dry Mix)

PRODUCT DESCRIPTION

DAP® All-Purpose Stucco Patch may be used to repair large holes and cracks in interior and exterior stucco surfaces. It's easy to mix formula blends naturally with existing stucco for a professional finish. Durable and permanent. Easy to tool and paint. Interior/exterior use.



PACKAGING	COLOR	UPC
25 lb. bag	White	7079810502

KEY FEATURES & BENEFITS

- Professional quality, for repairs in stucco surfaces
- Easy to tool and paint
- Durable
- Interior/Exterior use

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on stucco

APPLICATION

1. Surface must be free of grease, oil and other foreign matter. Sweep or blow surface with compressed air to remove all mud, dirt, dust and other loose debris.
2. Add stucco patch to clear water in clean container mixing 4 parts of powder to 1 part of water by volume. For a smoother finish, dip putty knife in water and lightly smooth spackling.
3. Let the mixture set for 15 minutes then re-stir until smooth. Do not mix more material than can be used in 1 to 2 hours. Discard any material that has begun to harden.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

4. Apply stucco patch with a clean putty knife or trowel. For fills over 1/4" deep apply 2 or more layers allowing each layer to dry before applying the next layer. Use a rubber float to blend patch with the existing stucco surface.

NOTE: Consult paint manufacturer's recommendations before decorating.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Working Time	1 to 2 hours
Setting Time	2 to 4 hours
Final Cure	3 days
Mixing Ratio	Add 5 pt. water to 25 lb. bag Stucco Patch
Coverage	10-12 sq. ft. with 1/4" thickness

CLEAN UP & STORAGE

- Wash skin and hands with soap and water.
- Cured material must be scraped or sanded away.
- Wash tools with water immediately after use.
- Be sure bag is closed and tightly sealed.
- Store powder in a cool, dry place.
- Do not store mixed material.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com