



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Patching Plaster

PRODUCT DESCRIPTION

DAP® Patching Plaster is a ready mixed, easy-to-use, general purpose patching material used to fill holes and cracks in plaster and drywall prior to painting. The product has a smooth working consistency, dries quickly with minimal shrinkage and sands easily. Recommended for interior use only.



PACKAGING	COLOR	UPC
Quart	White	7079852084

KEY FEATURES & BENEFITS

- Ready to use general purpose patching compound
- Fills holes and cracks in plaster and drywall prior to painting
- Dries quickly with minimal shrinkage
- Interior use

SUGGESTED USES

Ideal for filling holes and cracks in plaster and drywall surfaces

FOR BEST RESULTS

- Recommended for interior use only.
- Do not apply in temperatures below 50°F.
- Use sandpaper to dull glossy surfaces before repairing.
- Do not use on floors or as a caulk, sealant or joint filler over cracks & joints where expansion & contraction may occur.
- **DO NOT USE AS A SKIM COAT.**



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION

1. Widen cracks in plaster with a putty knife or utility knife to at least 1/4 inch in width and brush away loose particles.
2. Surface to be repaired must be clean, dry, structurally sound and free of foreign material.
3. Stir thoroughly before use.
4. Apply with a clean putty knife.
5. For a smoother finish, dip putty knife in water and lightly smooth plaster.

For repairs deeper than 1/4":

1. Apply two or more layers allowing the patch area to dry between applications.
2. Apply first coat to within a quarter-inch of surface and let set 4 to 6 hours.
3. Complete patch on the second coat and smooth.
4. Allow this coat to dry at least 24 hours before painting.
5. Drying times may vary depending on room temperature, humidity, and depth of fill.

For one-layer applications:

1. DAP Patching Plaster can be sanded or painted 1 to 5 hours after application depending on temperature, humidity, and depth of fill.
2. Wet sanding is recommended to avoid generation of dust.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Heavy bodied paste
Vehicle	Latex Emulsion
Volatile	Water
Filler	Various Inerts
Odor	Mild
Solids	70 % + 3% by weight
Weight per Gallon	15.1 lbs./gallon
Application Temperature	50°F Minimum
Service Temperature	-20°F to 120°F
Shelf Life	12 months
Freeze	Protect from freezing



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Dry Time	1 to 5 hours depending on temperature and relative humidity <i>(See special instruction for deep repairs)</i>
Painting	1 to 5 hours depending on temperature and relative humidity <i>(See special instruction for deep repairs)</i>

NOTE: These figures are approximate and may vary with climatic conditions

CLEAN UP & STORAGE

Wash tools immediately after use with water before product has set. Dried material must be mechanically scraped, chipped or ground away. Close container tightly and store any remaining powder in a cool, dry place.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com